



GLOBAL POSITION

Tecnologia: 4G


Servidores

 SP: 49.12.92.6 - dns.mine.nu | Porta = 5010

 AL: 168.119.25.88 - ese.mine.nu | Porta = 5010

 SC: 167.235.35.219 - sc.mine.nu | Porta = 5010

 PI: 167.235.34.85 - dns.alfarastreamento.com | Porta = 5010

 SP Sorocaba: 65.21.232.27 - sastracker.mine.nu | Porta = 5010

 MA: 65.21.249.189 - telensat.mine.nu | Porta = 5010

Comandos

Porta(s): 5010

Configuração Inicial

Comando 1: AT+XAPN=1,lf.br,lf,lf (**Comando APN - Exemplo de APN da Linksfield**)

Necessário alterar o comando de acordo com a APN utilizada

Comando 2: AT+XIP=49.12.92.6,5010,1 (**Comando para conexão do rastreador na plataforma**)

O IP/DNS devem ser substituídos de acordo com o servidor

Comando 3: AT+XDHC=25,1 (**Reporte por ângulo**)

Comando 4: AT+XHB=1,10,1 (**Tempo de Transmissão chave desligada**)

Comando 5: AT+XDRI=1,30,1 (**Tempo de Transmissão chave ligada**)