



MAXTRACK MXT160

Tecnologia: 2G


Servidores

 SP: 49.12.92.6 - dns.mine.nu | Porta = 7087

 AL: 168.119.25.88 - ese.mine.nu | Porta = 7087

 SC: 167.235.35.219 - sc.mine.nu | Porta = 7087

 PI: 167.235.34.85 - dns.alfarastreamento.com | Porta = 7087

 SP Sorocaba: 65.21.232.27 - sastracker.mine.nu | Porta = 7087

 MA: 65.21.249.189 - telensat.mine.nu | Porta = 7087

Por favor, utilizar apenas DNS, usar IP somente para rastreadores que se comunicam exclusivamente via IP

Comandos

Porta(s): 7087

Configuração Inicial

Comando 1: 0000,connection lf.br if if (**Comando APN - Exemplo de APN da Linksfield**)

Necessário alterar o comando de acordo com a APN utilizada

Comando 2: 0000,address dns.mine.nu 7087 0 dns.mine.nu 7087 0 (**Comando para conexão do rastreador na plataforma**)

O IP/DNS devem ser substituídos de acordo com o servidor!

Comando 3: 0000,ignoffstop 7200 (**Tempo de Transmissão chave desligada**)

Comando 4: 0000,ignon 30 (**Tempo de Transmissão chave ligada**)