



OBD2

Tecnologia: 2G


Servidores

 SP: 49.12.92.6 - dns.mine.nu | Porta = 6013

 AL: 168.119.25.88 - ese.mine.nu | Porta = 6013

 SC: 167.235.35.219 - sc.mine.nu | Porta = 6013

 PI: 167.235.34.85 - dns.alfarastreamento.com | Porta = 6013

 SP Sorocaba: 65.21.232.27 - sastracker.mine.nu | Porta = 6013

 MA: 65.21.249.189 - telensat.mine.nu | Porta = 6013

Comandos

Porta(s): 6013

Configuração Inicial

Comando 1: 8030000 transmeet.br claro claro (**Comando de APN - Exemplo de APN da transmeet**)

Necessário alterar o comando de acordo com a APN utilizada

Comando 2: 8040000 dns.mine.nu 6013 (**Comando para conexão do rastreador na plataforma**)

O IP/DNS devem ser substituídos de acordo com o servidor

Comando 3: 8050000 30 (**Tempo de transmissão em movimento**)

Comando 4: 8090000 7200 (**Tempo de transmissão parado**)

Comando 5: 7100000 (**Habilitar transmissão via GPS**)

Comando 6: 8960000 W0 (**Configuração do fuso horário**)